



CMRFID
Technology CO., Ltd

CMRFID (California)

✉ allen@cmrfid.com
☎ +1 213 393 0528

CMRFID (Brazil)

✉ Rinaldo@cmrfid.com
☎ +55 11 964337000

CMRFID (Dubai)

✉ Iman@cmrfid.com
☎ +48 574 549 256

CMRFID (Shanghai)

✉ Javier@cmrfid.com
☎ +86 18601658083

WIND SHIELD TAG (TAMPER PROOF)

Product Introduction

- 860-960 MHz frequency range for worldwide application. Tag protocol is EPC class 1 generation 2
- Uviolet resistant, anti-solvent to avoid sunlight damage to the chip
- Antenna destroyed once stick off the window
- 3M adhesive instead of traditional bonding
- Double side logo printing to ensure the logo can be seen from different direction
- Can read and write data into tag's user memory bank
- Good reading performance - good reading distance with fast reading speed

FEATURES

1. ETC self-service system
2. Smart parking system
3. Logistics and warehousing management
4. Product anti-counterfeiting detection
5. Others: anti-cheating weighing system, the management of transport vehicles, product line management etc.

| Specification | |
|--------------------------|--|
| Protocol | EPC class 1 generation 2/ISO 18000-6C |
| Frequency | 860 —960MHZ |
| Read distance | 6-10m (depending on reader and the exact environment) |
| Anti-collision mechanism | Yes, suitable for cards pool reading (read several cards at same time) |
| Using area | 916+512bits |
| Read/write | Can read/write data into the tag |
| Package material | Coated paper |
| Installation | Easy stick |
| Storage year | >10years |
| Wiping times | >100, 000 times |
| Working temperature | -40°C ~+85°C |
| Size | 45*110MM and customization size is available |

